

Type:	Standard patch panel	
Ref:	PSS-A0	REV: 1.2
Date:	07.07.2016	AL
Modification:	30.04.2021	DP

Distribution solutions

FIBRAIN PSS-A0 19" Standard patch panel



DESCRIPTION:

- Height 1U
- Full extension shelf with integrated front plate
- Simple construction
- Available for 12 or 24 adapters SC sx/ SC dx/ FC / ST
- Cable central member holder
- Available in equipped version with adapters and pigtails

TECHNICAL SPECIFICATION:

Technical data	PSS-A0
Height	1U (44mm)
Width	19" (482,6mm)
Depth	201mm
Maximum splice cassette quantity	3
Material	Powder coated steel / plastic guides



Type:	Standard patch panel	
Ref:	PSS-A0	REV: 1.2
Date:	07.07.2016	AL
Modification:	30.04.2021	DP

Distribution solutions

ORDERING INFORMATION:

PSS-A0-AABBC-DDEFG-HHIJKLL-MN-OOP-RS

AA – Height	01 – 1U (grey RAL7035) B1 – 1U (black RAL9005)
BB – Faceplate type	01 - 24x ST/FC 02- 24x SC SX/E2000 SX / LC DX 03- 24x SC DX 04- 12x SC DX 05- 12x SC SX / E2000 SX / LC DX 06- 12x ST/FC
C – Lock	0 – plate without lock
DD – Number of adapters	0 – 12
E – Adapter Class	1 – Standard One-Piece (Standard for E2000, FC, ST) 2 – Premium Super One-Piece 3 – Premium One-Piece with Internal shutter 4 – Premium (applies to FC, ST)
F – Adapter type	1 – SC 2 – SCA 3– E2000 4 – E2000 APC 5- LC 6- LCA 7– FC 8– FCA 9 – ST
G – Transmission type	1 – SM 2 – MM (beige @SC/LC, black @E2000) 3 – MM OM3 (aqua @SC/LC) 4 – MM OM4 (violet @SC/LC)
HH – Number of pigtails	0 – 48
I – Fibre type	A – G.652D B – G.655 C – G.656 D – G.657A1 E – G.657A2 F – G.657B2 G – G.657B3 H– MM OM1 I– MM OM2 K – MM OM3 L – MM OM4
JJ – Connector type	01 – SC 02 - SCA 03– LC 04- LCA 05 – FC 06- FCA 07– E2 08– E2A 09 – ST
K – Pigtail Class	G – Gold T – Titanium
LL – Colour standard	01 – for pigtails with 0.9mm tube in yellow 02 – for pigtails with 0.9mm tube in orange 03 – T TELECOM (according to IEC60304) 04 – T1 TELECOM (according to 60304/tab. 3 & ZN-11/TPSA-005-02) 05 – T2 TELECOM (according to EIA 598A) 06 – D DATACOM (according to DIN VDE 0888 & IEC 60304) 07 – D1 DATACOM (according to IEC 60304, TIA/EIA 598-A, TIA/EIA 598-C) 08 – for pigtails with 0.9mm tube in aqua colour 09 – for pigtails with 0.9mm tube in green

Type:	Standard patch panel	
Ref:	PSS-A0	REV: 1.2
Date:	07.07.2016	AL
Modification:	30.04.2021	DP

Distribution solutions

M – Number of cassettes

N – Cassette type

OO – Number of protection sleeves

P – Protection sleeve type

R – Number of cable glands

S – Gland type

10 – for pigtails with 0.9mm tube in purple

11 – for pigtails with 0.9mm tube in blue

1-3

1 – SCM-A-12H

2 – SCM-A-24H

0-48

1 – 45 mm

1-2

1 – PG13.5

2 – PG16

This document and the statements contained in it, are not intended for customers within the meaning of Civil Code. The information submitted in this document is to our knowledge and belief true at the time of issue, however, we do not assume any liability whatsoever for its accuracy, and completeness. This document is for informational purposes on an "as is" basis only, and Fibrain reserves the right to change its contents at any time without prior notice. The specification cannot in any case be considered an offer within the meaning of the Civil Code and is not contractually valid unless specifically authorized by Fibrain. Before using this product, its buyer and/or user has to make sure that it is suitable for the intended use. All liability issues related to this product are subjected to the seller's separate Terms of Sale or the terms and conditions agreed with the Fibrain representative or distributor.