

## Passive Optical Networks

xWDM/xPON CEx series multiplexers



### INTRODUCTION:

xWDM/xPON multiplexers can be applied in expanding of an existing PON network to new services or protocols. xWDM/xPON solutions family consists of devices compliant with the ITU-T G.984.5 recommendation as well as dedicated solutions adapted for the Customer's needs. High quality components ensure very high operation stability of xWDM/xPON multiplexers in the whole spectral range and perfect thermal stability. xWDM/xPON multiplexers are available both in a version without connectors (intended for splicing) and with any connector type.

### APPLICATIONS:

- WDM systems
- FTTH access networks
- Cable networks and HFC
- Other optical telecommunication networks

### FEATURES AND ADVANTAGES:

- High thermal stability of parameters.
- Low insertion and polarization losses.
- High interchannel isolation.
- Available with any type of fiber optic connectors.
- Available non-standard solutions with specialized functionalities.

## Passive Optical Networks

### TECHNICAL SPECIFICATIONS:

Insertion loss and isolation:

Multiplexer <sup>1</sup>	Protocol/service	Spectral range	Max. insertion loss <sup>2</sup>	Isolation
CEx.1	GPON	1290-1330 nm 1480-1500 nm	0.7 dB	≥ 25 dB
	XG-PON1	1260-1280 nm 1575-1580 nm	1.2 dB	≥ 25 dB
	NG-PON2	1524-1544 nm 1596-1625 nm	1.1 dB	≥ 16 dB
CEx.3	GPON	1290-1330 nm 1480-1500 nm	0.7 dB	≥ 25 dB
	VIDEO	1550-1560 nm	1.8 dB	≥ 16 dB
	NG-PON2	1524-1544 nm 1596-1625 nm	2.0 dB	≥ 25 dB

<sup>1</sup>Nomenclature according to ITU-T G.984.5 recommendation

<sup>2</sup>Additional insertion losses in the case of multiplexers with connectors: +0.4 dB

Other parameters:

Parameter	Unit	Value
PDL	dB	≤0.1
Directivity	dB	≥55
RL	dB	≥50
Max. input power	dBm	23
Temp. operating range	°C	-10/+70
Temp. storage range	°C	-40/+85
Fiber type	-	G.652.D

### ORDERING INFORMATION:

Series	Quality	Fiber type	Optical functionality	Monitoring port	Multiplexer type	Cable type	Pigtail length	Housing	Connector in	Connectors out
XW	G0	1 - G.652D	SMU - Standard Mux	0 - no port	CEx.1	20 - 2.0 mm cable	LL - length in dm	1-SST 44x28x7 mm	ST	ST
		2 - G.657A1	CMU - Compact Mux	1 - monitor 1% standard uni-di	CEx.3	25 - 250 μm fiber	12 - 1.2 m	2-ABS 100x80x10 mm	SC	SC
		3 - G.657A2		2 - monitor 1% standard bi-di		90 - 900 μm tube		3-ABS 120x80x18 mm	SCA	SCA
		4 - G.655		3 - monitor 5% standard uni-di				4-ABS 140x115x15 mm	FC	FC
				4 - monitor 5% standard bi-di					FCA	FCA
				5 - monitor 5% flat uni-di					LC	LC
				6 - monitor 5% flat bi-di					LCA	LCA
									E20	E20
									E2A	E2A

Example reference: XW-G0-3-SMU-0-CEx.3-20-10-2-SCA-SCA – CEx.3 SMU multiplexer, PREMIUM quality, without power monitoring port, G.657.A2 fiber, 1 m pigtail length, 2.0 mm tube, ABS housing if dimensions 100x80x10 mm, SCA connectors.

#### Important notice

Buyer and/or user of this product has to make sure before using this product that it is suitable for the intended use. All questions of liability relating to this product are subject – in accordance with the prevailing – to the Terms of Sales of the selling Fibrain subsidiary.