

Anchoring tension clamp for round cables AT-UO-xxxxL



*illustrative photo

DESCRIPTION

- Minimum tensile strength 4000 N
- Automatic tightening, conical type
- Opening bail and unlosable, easy to assemble
- Maximum span 100 m
- Tool-free installation
- Harmless for the outer sheath (coating) of the cable
- Available versions for different cable dimensions

TECHNICAL SPECIFICATION

Weight [kg]	0,31		0,32		
Cable diameter range [mm]	7-10	10-12	11-15	14-16	15-18
Housing material	High resistance aluminium alloy				
Wedge material	UV protected thermoplastic				
Bail material	Stainless steel				
Temperature	-20°C - +80°C				

ORDERING

AT-UO10L - Anchoring clamp for ADSS cables, span up to 100m, cable diameter range 7-10mm
 AT-UO12L - Anchoring clamp for ADSS cables, span up to 100m, cable diameter range 10-12mm
 AT-UO14L - Anchoring clamp for ADSS cables, span up to 100m, cable diameter range 11-15mm
 AT-UO16L - Anchoring clamp for ADSS cables, span up to 100m, cable diameter range 14-16mm
 AT-UO18L - Anchoring clamp for ADSS cables, span up to 100m, cable diameter range 15-18mm