

FTTH Solutions

Type: Outdoor fiber optic cabinets

Ref: FDH-F3-x, see ordering information REV: 1.2

Date: 22.08.2019 DP

Modification: 12.04.2021 DP

Fibrain outdoor fiber optic cabinet FDH-F3



DESCRIPTION:

- Hinged plate with adapter panel
- Dedicated holders for cables / microducts entering the cabinet
- Maximum capacity of 96 splices
- Adapter panel for 85 SC adapters
- Possibility of mounting 6 splitters in Blackbox / Alubox housing
- Possibility of storage up to 5m of cable stock
- Optional lock for front door
- Door open at an angle of 180°

TECHNICAL SPECIFICATION:


Technical data	FDH-F3
Maximum number of splices	96
Maximum number of adapters	85
Adapter type	SC, LC DX
Maximum number of splitters (Blackbox, Alubox)	6
Cabinet dimensions with basis (W)x(H)x(D) [mm]	400x1416x266
Front door dimensions [mm]	400x456
Cabinet height above the ground	756
Flammability class	V0
Internal organizer material*	Galvanized steel
Housing material	Fibreglass + polyester
Impact protection	IK10
Ingress protection	IP54

^{*}aluminium available as an option



FTTH Solutions

Type:	Outdoor fiber optic cabinets	
Ref:	FDH-F3-x, see ordering information	REV: 1.2
Date:	22.08.2019	DP
Modification:	12.04.2021	DP



Hinged plate with adapter panel

Adapter panel for 85 SC adapters SC SX / LC DX

Dedicated holders for cables / microducts entering the cabinet

Holder for cables / microducts

Maximum capacity of 96 splices (4 cassettes SCM-A-24H)

Possibility of mounting 6 splitters in Blackbox / Alubox housing

Removable front panels of cabinet



FTTH Solutions

Type:	Outdoor fiber optic cabinets	
Ref:	FDH-F3-x, see ordering information	REV: 1.2
Date:	22.08.2019	DP
Modification:	12.04.2021	DP

ORDERING INFORMATION:

ORDERING INFORMATION:			
FDH-F3-AABC-DDEFGHH-IJK-LM-N-O-PP-R	Ordering syntax:		
AA – Adapter quantity	0 – 85		
B – Adapter class	0 – none 1 – Standard One-Piece 2 – Premium One-Piece with internal shutter		
C – Adapter type	0 – none 1 – SC/PC 2 – SC/APC 3 – LC/PC 4 – LC/APC		
DD – Pigtail quantity	0 - 85		
E – Fiber type	A – G.652D B – G.655 C – G.656 D – G.657A1 E – G.657A2 F – G.657B2 G – G.657B3		
F – Connector type	1 – SC/PC 2 – SC/APC 3 – LC/PC 4 – LC/APC		
G – Pigtail class	G – Gold		
HH- Colour identification	01 – pigtails with yellow 0,9mm buffer 02 – T TELECOM (acc. to IEC60304)		
I - Splitter quantity	0-6		
J – Splitter housing	0 – none 1 – Alubox 2 – Blackbox		
K – Splitter type	0 - none 1 - 1:2 2 - 1:4 3 - 1:8 4 - 1:16 5 - 1:32		
L – Splice cassette quantity	0 – 4		
M – Splice cassette type	0 – none 1 – SCM-A-12H 2 – SCM-A-24H		
N – Expanded clay	0 – none 1 – equipped		
O – Lock	0 – none 1 – equipped		
PP – Cabinet colour	GY – grey		
R – Internal organizator material	S – steel A - aluminum		

This document and the statements contained in it, are not intended for customers within the meaning of Civil Code. The information submitted in this document is to our knowledge and belief true at the time of issue, however, we do not assume any liability whatsoever for its accuracy, and completeness. This document is for informational purposes on an "as is" basis only, and Fibrain reserves the right to change its contents at any time without prior notice. The specification cannot in any case be considered an offer within the meaning of the Civil Code and is not contractually valid unless specifically authorized by Fibrain. Before using this product, its buyer and/or user has to make sure that it is suitable for the intended use. All liability issues related to this product are subjected to the seller's separate Terms of Sale or the terms and conditions agreed with the Fibrain representative or distributor.