

Type:	Splice protection sleeve	
Ref:	FB7442	REV: 1.1
Date:	25.03.2014	At
Modification:	02.04.2021	DP

## Distribution fiber

### Fibrain FB7442 Heat-shrink splice protection sleeve 45mm



#### DESCRIPTION:

- Transparent sleeve
- Fulfills the requirements of UL224, MIL-I-23053, GR-1380-CORE, ZN-96 TPSA-006 standards
- In accordance with RoHS Directive
- Min. shrink temperature: 110°C
- Max. shrink time: 60s

#### TECHNICAL SPECIFICATION::

	L	Lp	D	Dp	d
FB7442	45	41	2,4	1	1,4

L - Sleeve length after heating,

Lp - Pin length

D - Sleeve diameter after heating

Dp - Pin diameter

d - Inner hole diameter before shrink

#### ORDERING INFORMATION::

**FB7442**      45MM HEAT-SHRINK SPLICE PROTECTION SLEEVES

This document and the statements contained in it, are not intended for customers within the meaning of Civil Code. The information submitted in this document is to our knowledge and belief true at the time of issue, however, we do not assume any liability whatsoever for its accuracy, and completeness. This document is for informational purposes on an "as is" basis only, and Fibrain reserves the right to change its contents at any time without prior notice. The specification cannot in any case be considered an offer within the meaning of the Civil Code and is not contractually valid unless specifically authorized by Fibrain. Before using this product, its buyer and/or user has to make sure that it is suitable for the intended use. All liability issues related to this product are subjected to the seller's separate Terms of Sale or the terms and conditions agreed with the Fibrain representative or distributor.