

Patch cord HD RJ45, Cat.6A, U/FTP, LSZH, 500MHz



FEATURES:

- Cat.6A performance according to: ISO 11801-x, EN 50173-x, ANSI/TIA 568.2-D
- Shielded construction
- Connector compact size
- Color coding
- The highest quality guaranteeing large margins of transmission parameters over the requirements of the standards
- The best performance in conjunction with FibrainDATA RJ45 connection modules
- Component complies to IEC 60603-7-51
- Wire separation provided due to unique design
- Stabil boot
- Pin contact area covered with gold layer
- Minimal wire overlength due to connector construction
- Shielded connector providing EMC 360° protection
- Wire scheme acc.568B
- RFID ready

TECHNICAL PARAMETERS:

Standardization	ISO 11801-x, EN 50173-x, TIA 568.2-D, IEC 60603-7-51
PoE	IEEE 802.3af/802at and 802bt type 3 and type 4 (do 100W)
Operation temperature range	-10 °C ÷ 60 °C
Storage temperature range	-40 °C ÷ 70 °C
Transmission performance	Cat.6A
Shielding	Yes
Housing material	Plastic + shield
Max. Current rating [A]	1,5
Max. Voltage [VDC]	1000
Stranded wire diameter	AWG 26/7
Cable diameter	5,7 mm
Jacket material	LSZH
Wire diagram	568B
Jacket color	Grey(GY)

ORDERING:

XRPxxxx.GY220 Cat. 6A, length xxxx cm, U/FTP, TIA 568B, grey jacket color, turquoise shielded connector

This document and the statements contained in it, are not intended for customers within the meaning of Civil Code. The information submitted in this document is to our knowledge and belief true at the time of issue, however, we do not assume any liability whatsoever for its accuracy, and completeness. This document is for informational purposes on an "as is" basis only, and Fibrain reserves the right to change its contents at any time without prior notice. The specification cannot in any case be considered an offer within the meaning of the Civil Code and is not contractually valid unless specifically authorized by Fibrain. Before using this product, its buyer and/or user has to make sure that it is suitable for the intended use. All liability issues related to this product are subjected to the seller's separate Terms of Sale or the terms and conditions agreed with the Fibrain representative or distributor.