


Photonics

| Туре: | High Reflection Termination | REV: 1.0 | |
|---------------|-----------------------------|----------|--|
| Date: | 13/04/2018 | OJ | |
| Modification: | | | |

High Reflection Termination



Fibrain High Reflection Patchcords are characterized by uniform high return loss in the whole CWDM wavelength range. Their function is to reflect as much light as possible, which is required in some polarization mode dispersion measurement schemes. They are polarization independent passive components. Each patchcord is delivered with a test report. The patchcords are based on various fiber types (G.652.D, G.657.A2, etc.) and their length and connectors are chosen based on customer's order. Detailed selection of the manufacturing components ensures the highest quality of the connectors.

APPLICATIONS

- ✓ Testing systems
- Polarization mode dispersion and chromatic dispersion measurements
- ✓ Measuring devices calibration

ADVANTAGES & FEATURES

- ✓ 1250 nm 1650 nm operating range
- ✓ Available as a patchcord with any connector
- ✓ Return loss < 1 dB</p>
- ✓ Each HRT is measured individually

TECHNICAL SPECIFICATIONS:

| Parameter | Value |
|-------------------------|-------------------------------------|
| Reflected wavelengths | 1250-1650 nm |
| Return loss | <1 dB |
| PDL | <0.5 dB |
| Operating temperature | 0 to +45 °C |
| Storage temperature | -40 to +85 °C |
| Optical operating power | 500 mW |
| Fiber type | G.652.D, G.657.A1, G.657.A2, others |

PACKAGING:

The patchcords are individually packed in string bags.



Photonics

| Type: | High Reflection Termination | REV: 1.0 | |
|---------------|-----------------------------|----------|--|
| Date: | 13/04/2018 | OJ | |
| Modification: | | | |

ORDERING INFORMATION:

| Series | Quality | Fiber type | Fiber length | Cable type | Connector type | Cable | color |
|--------|---------|------------|--------------|-------------|----------------|-------|-------|
| HRT | G0/G1 | 1-G.652.D | 0 - 0.5 m | 25 – 250 μm | ST | | OR |
| | | 2-G.657.A1 | 1 - 1 m | 90 – 900 μm | SC | | Υ |
| | | 3-G.657.A2 | 2 - 2 m | 20 – 2.0 mm | SCA | | GR |
| | | 4-G.657.B1 | | 30 – 3.0 mm | FC | | GY |
| | | 5-G.657.B2 | | | FCA | | BL |
| | | 6-G.657.B3 | | | LC | | BK |
| | | X-other | | | LCA | | ٧ |
| | | | | | E20 | | R |
| | | | | | E2A | | W |
| | | | | | XX-pigtail | | |
| | | | | | x-other | | |

Example: HRT-G0-1-1-20-SCA - Fibrain High Reflection Termination based on G.652.D fiber, 1 m fiber length, 2.0 mm cable, SC APC.

Important notice
Buyer and/or user of this product has to make sure before using this product that it is suitable for the intended use. All questions of liability relating to this product are subject – in accordance with the prevailing – to the Term of Sale of the selling Fibrain subsidiary.