

Fibrain extendable Patch panel HD 0.5U for 48 splices



DESCRIPTION:

- Height 0.5U
- Maximum adapter capacity: 48xSC SX/ LC DX/ E2000 (4 adapter holders)
- Maximum splice capacity: 48
- Full extension on telescopic rails
- Front plate equipped with handles for easy opening
- Range of supported connectors: LCdx, SC, E2000 – MM/SM

TECHNICAL SPECIFICATION:

Height	0.5U
Width	19"
Depth	284mm
Material	Powder painted steel

CONFIGURATION:

Number of adapter slots	LC DX adapter number	SC, E2000 adapter number
6	6	6
12	12	12
24	24	24
48	-	48



Type:	HD fiber optic patch panel	
Ref:	XCUx, see order information	REV: 1.1
Date:	07.09.2022	DP
Modification:	05.07.2024	DP



ORDERING:

XCU10-AB-CD

Ordering syntax

Patch panel equipped in 2 SCM-A-24H splice cassettes, quantity, type of adapters and pigtails according to syntax below:

A – Connector type	2 – LC PC 3 – LC APC 4 – SC PC 5 – SC APC 6 – E2000 PC 7 – E2000 APC
B – Connector class	1 - Gold
C – Fiber type	A – MM OM1 B – MM OM2 C – MM OM3 D – MM OM4 H – MM OM5 I – 657A1 J – 657A2
D – Number of ports	A – 6 B – 12 C – 24 D – 48

This document and the statements contained in it, are not intended for customers within the meaning of Civil Code. The information submitted in this document is to our knowledge and belief true at the time of issue, however, we do not assume any liability whatsoever for its accuracy, and completeness. This document is for informational purposes on an "as is" basis only, and Fibrain reserves the right to change its contents at any time without prior notice. The specification cannot in any case be considered an offer within the meaning of the Civil Code and is not contractually valid unless specifically authorized by Fibrain. Before using this product, its buyer and/or user has to make sure that it is suitable for the intended use. All liability issues related to this product are subjected to the seller's separate Terms of Sale or the terms and conditions agreed with the Fibrain representative or distributor.